



Waveguide Pressurisation Product Selection guide

	12434	12435	12436	12437/L	12445	12446
Dry Air Delivery	<i>30 ft/hr</i>	5 ft/hr	<i>7 ft/hr</i>	35 ft/hr	<i>5 ft/hr</i>	6 ft/hr
	<i>850 l/hr</i>	140l/hr	<i>200 l/hr</i>	1000 l/hr	<i>140l/hr</i>	170l/hr
Output Pressure	<i>0.5-5 psi</i>	0.5-5 psi	<i>0.5-5 psi</i>	0.5-5 psi	<i>0.5-5 psi</i>	0.2 or 0.6 psi
	<i>35-345 mbar</i>	35-345 mbar	<i>35-345 mbar</i>	35-1000 mbar	<i>35-345 mbar</i>	15 or 40 mbar
Outlet Dewpoint	<i>-35°C</i>	-35°C	<i>-35°C</i>	-35°C	<i>-35°C</i>	-45°C
No. of Outlets	<i>3</i>	3	<i>3</i>	5 or 10	<i>3</i>	6
Air Receiver	<i>Yes</i>	Yes	<i>Yes</i>	Yes	<i>Yes</i>	Yes
Sound Damping	<i>No</i>	No	<i>No</i>	Yes	<i>No</i>	No
Height (mm)	<i>820</i>	133.3	<i>133.3</i>	960	<i>380</i>	220.5
Width (mm)	<i>320</i>	482	<i>482</i>	440	<i>500</i>	441.5
Depth (mm)	<i>200</i>	378	<i>378</i>	330	<i>159</i>	240
Weight (kg)	<i>30</i>	17	<i>17.5</i>	60	<i>20</i>	20
Voltage	<i>230v</i>	230v	<i>230v</i>	230v	<i>230v or 115v</i>	230v or 48v
Mounting Method	<i>Wall/ Floor</i>	Rack	Rack	Floor	Wall	Rack