



Cable Pressurisation Product Selection guide

	12377	12405	12434	12255	12269	12437/H	12440	12450
Dry Air Delivery	<i>30 ft/hr</i>	625 ft/hr	<i>30 ft/hr</i>	100 ft/hr	<i>185 ft/hr</i>	35 ft/hr	<i>170 ft/hr</i>	35 ft/hr
	<i>850 l/hr</i>	17500 l/hr	<i>850 l/hr</i>	2800 l/hr	<i>5200 l/hr</i>	1000 l/hr	<i>4800l/hr</i>	1000 l/hr
Output Pressure	<i>3-15 psi</i>	3-15 psi	<i>0.5-5 psi</i>	3-15 psi	<i>3-15 psi</i>	3-15 psi	<i>N/A</i>	<i>N/A</i>
	<i>200-1000 mbar</i>	200-1000 mbar	<i>35-345 mbar</i>	200-1000 mbar	<i>200-1000 mbar</i>	35-1000 mbar	<i>N/A</i>	<i>N/A</i>
Outlet Dewpoint	<i>-35°C</i>	-40°C	<i>-35°C</i>	-40°C	<i>-40°C</i>	-35°C	<i>-35 °C</i>	-35°C
No. of Outlets	<i>1</i>	Up to 140	<i>3</i>	Up to 40	<i>Up to 80</i>	5 or 10	<i>1</i>	<i>1</i>
Air Receiver	<i>No</i>	Yes	<i>Yes</i>	Yes	<i>Yes</i>	Yes	<i>No</i>	Yes
Sound Damping	<i>No</i>	Yes	<i>No</i>	Yes	<i>Yes</i>	Yes	<i>Yes</i>	Yes
Height (mm)	<i>600</i>	2110	<i>820</i>	1600	<i>2237</i>	960	<i>1190</i>	800
Width (mm)	<i>330</i>	1350	<i>320</i>	546	<i>560</i>	440	<i>610</i>	440
Depth (mm)	<i>325</i>	740	<i>200</i>	686	<i>740</i>	330	<i>600</i>	330
Weight (kg)	<i>30</i>	421	<i>30</i>	190	<i>210</i>	60	<i>123</i>	55
Voltage	<i>230v or 115v</i>	380v 3-phase	<i>230v</i>	230v or 115v	<i>230v or 115v</i>	230v	<i>230v</i>	230v
Mounting Method	<i>Floor</i>	Wall/ Floor	<i>Floor</i>	Floor	<i>Wall</i>	Rack	<i>Floor</i>	Wall/ Floor