



Series 95



Series 95 Ordering Chart

Weatherproof Enclosure (for electric switch only) Yes W No No code required	
Electric Switch Code See Electric Switch Page	
No. of Positions 2,3,4 (No code required if unrestricted)	
Mounting Panel (No code required) Base Mounting Plate 1	
Connections 1/2" NPT Female F8 1/2" Spigot S8 3/8" Spigot S7	
Operators L ever K ey Lever Type	
Port Code	
No. of Banks 1 to 4	
Class (See Below)	
<p>Class P: Brass Body Stainless Steel Spindle Acetal Resin Stems Fluoro Elastomer Seals</p> <p>Class R: Brass Body Stainless Steel Spindle PTFE Stems Fluoro Elastomer Seals</p> <p>Class S: Stainless Steel Body Stainless Steel Spindle Acetal Resin Stems Fluoro Elastomer Seals</p> <p>Class T: Stainless Steel Body Stainless Steel Spindle PTFE Stems Fluoro Elastomer Seals</p>	

EXAMPLE 95 P 1 02 L F8 1

High Flow Capacity
Series 95 Valves offer a higher flow capacity than their sister products, 40 & 60 Series.

Versatility
Used in a wide variety of applications this robust product is particularly useful in emergency shut down applications.

Permutations
With the choice of operative, permanently open and permanently closed ports in any of the four positions, plus a spindle with one flat, two adjacent, two opposite, or three flats, the number of permutations in just one bank is clearly enormous.